

DC Gear Motor


P37ZFP510

DC Gear Motor

General Specifications

Ø37 mm
 24 VDC
 588.4 mNm

Customized solutions on request.



Electrical Specifications

Model	Voltage	No-load Current	No-load Speed	Rated Current	Rated Speed	Rated Torque	Max. Momentary Tolerance Torque	Gear Ratio	L
	VDC	A	rpm	A	rpm	mNm			mm
P37JPF3429-18220-10	12	0.16	600	0.45	520	39.2	1.2	1/10	17
P37JPF3429-18220-30	12	0.16	200	0.45	175	98.1	3.0	1/30	24
P37JPF3429-18220-90	12	0.16	66	0.45	57	225.6	7	1/90	24
P37JPF3429-18220-150	12	0.16	40	0.45	34.6	343.2	11	1/150	26.5
P37JPF3429-18220-270	12	0.16	22	0.45	19	588.4	18	1/270	26.5
P37JPF3429-18220-450	12	0.16	13	0.45	10	588.4	18	1/450	29
P37JPF3429-18220-810	12	0.16	7	0.45	6	588.4	18	1/810	29
P37JPF3429-15441-10	24	0.11	600	0.27	520	39.2	1.2	1/10	17
P37JPF3429-15441-30	24	0.11	200	0.27	175	98.1	3.0	1/30	24
P37JPF3429-15441-90	24	0.11	66	0.27	57	225.6	7	1/90	24
P37JPF3429-15441-150	24	0.11	40	0.27	34.6	343.2	11	1/150	26.5
P37JPF3429-15441-270	24	0.11	22	0.27	19	588.4	18	1/270	26.5
P37JPF3429-15441-450	24	0.11	13	0.27	10	588.4	18	1/450	29
P37JPF3429-15441-810	24	0.11	7	0.27	6	588.4	18	1/810	29

Typical values at ambient temperature of approx. 20°C. Tolerance ±10%.

Mechanical Dimensions

